



## Product Information

|                        |                                 |
|------------------------|---------------------------------|
| Ibstock Code:          | A5210A                          |
| Type:                  | Wirecut                         |
| Facing Description:    | Smooth                          |
| Dry Brick Weight (kg): | 2.4kg                           |
| Pack Quantity:         | 520                             |
| Packaging (standard):  | Shrinkwrapped on pallets (wood) |
| Factory:               | Imported                        |
| EPD:                   |                                 |

## Technical Specification (to BS EN 771-1)

|  |                       |
|--|-----------------------|
| Brick Dimensions (L x W x H mm):                       | 215x102x65            |
| Size Tolerances Mean & Range:                          | T2 R2                 |
| Configuration:   | Vertically Perforated |
| Voids (%):   | NPD                   |
| Compressive Strength (N/mm²):                          | 40                    |
| Active Soluble Salts:                                  | S2                    |
| Water Absorption (% weight):                           | 6                     |
| Durability:  | F2                    |
| Gross Dry Density (Sound Insulation) (Kg/m³):          | 1300                  |
| Equivalent Thermal Conductivity "K" value 5% Exposed:  | 1.12                  |
| Initial Rate of Absorption (Suction Rate) (Kg/m²/min): | NPD                   |
| EAN:   | n/a                   |